



PTC 113 S

Door entry phone “hands-free”, vandal resistant:

- meets the requirements for accessibility for people with disabilities
- with three programmable direct call buttons

The PTC 113 S can be connected to:

- the public analogue telephone network or a PABX,
- an AMPHITECH GSM-interface for voice communication,
- an IP to analogue converter for voice communication

Functions

- Telephone

Technical data

- 3 direct call buttons with programmable numbers
- 3 labelholders (for renewable labelling)
- 1 relay for door open command or remote control of external elements (lighting, camera, etc...)
- Automatic test call handling
(AMPHITECH central station equipment **ORA** for call reception and test call management)
- Communication time programmable from 1 to 9 minutes or 30 minutes
- Local or remote programming
- 12-30 VDC power supply required
- Consumption 350 mA max
- Mains failure information provided by AMPHITECH power supply unit
- Technical call in case of mains failure if used with an AMPHITECH power supply unit
(AMPHITECH central station equipment **ORA** for call reception and management)

Mechanical design

- Surface mount
- Dimensions 180 x 95 x 30 mm
- Degree of protection: IP 55 - IK 08
- Temperature range: -20° to +40°C
- Heating element with thermostat
- Stainless steel face plate 2.5 mm, ZAMAK housing

Options and accessories

- Power supply unit BAS 1202 - With battery back-up, with information “power failure”
- Power supply unit 1703 - Without battery back-up, without information “power failure”

